

## **HGQBSLJ-N**

#### Basic Information

Place of Origin: CHINA
Brand Name: THOBO
Minimum Order Quantity: 50



## Product Specification


• Highlight: shock absorber machine,

0.8MP Shock Absorbing Equipment

#### **Product Description**

This equipment is designed to detect the airtightness of the welded end of the bottom cover and the

peripheral welded parts of the automobile shock absorber liquid storage cylinder assembly. The leak test type is a horizontal full submersible type. After passing through the sealed port, the entire workpiece is submerged in water, and then compressed air is filled into the assembly. The welding workpiece's airtightness is judged by observing whether there are bubbles overflowing on the water surface. The time for sinking, airtightness detection, and control can be adjusted using a hand pull switch.



S/N	Item	Parameter	Remark s
1	Reservoir diameter φ D	φ30 ~ φ65mm	
2	Tank assembly length L	100~550mm	
3	Maximum outer diameter of spring disc φ D1	≤280mm	
4	Maximum detection pressure	0.8MP	

# Yuhuan Qizhong Trading Co., Ltd



008619957616998



jessieqizhong@groupmodified.com



@ groupmodified.com

No.16 Guangyi road, Damaiyu street, Yuhuan city, Taizhou, Zhejiang, China.