

## **HGHANM-c**

## Basic Information

Place of Origin: CHINA
Brand Name: THOBO
Minimum Order Quantity: 50



## Product Specification

Highlight: 30KN shock absorber machine,
 6MPah shock absorber machine

#### **Product Description**

This equipment is for automobile shock absorber piston rod valve nut tightening and riveting and design of special equipment. The equipment is divided into two parts: tightening station and riveting station. The touch screen controller is used to operate, set, and tighten the equipment. The tightening machine is used to tighten the nut with a preset torque, and then it is manually transferred to the riveting station. The riveting head is driven by hydraulic force to riveting the end of the connecting rod to prevent the nut from loosening. When riveting, the detection system detects and determines the riveting state through the pressure sensor and the displacement sensor, and alarms the parameters and the workpiece that exceeds the difference.



S/N	Item	Parameter	Remarks
1	Piston rod diameter φ d	φ8 ~ φ28mm	
2	Piston rod assembly length L	150~500mm	
3	Tightening clamping force	30KN(6MPa )	
4	Riveting force	18KN(6MPah)	
5	Tightening machine	Optional as required	

# THOBO Yuhuan Qizhong Trading Co., Ltd







@ groupmodified.com

No.16 Guangyi road, Damaiyu street, Yuhuan city, Taizhou, Zhejiang, China.